

**FEATURES:**

- Comply with RoHS standard, UL1950, IEC950 safety procedures
- Wide voltage input range, broadband noise filtering; Low ripple output
- Typical efficiency 82%
- High isolation voltage, short circuit, overload, overheat protection self-recovery
- Miniaturized design
- Fast dynamic response
- Size: 139\*108\*29mm
- Weight: 650g
- Widely used in military, communications, industrial control, transportation, electric power, new energy and scientific research and experiment and other fields


**Selection Guide**

Part No.	INPUT		OUTPUT				CapacitiveLoad(μF)
	Norminal (VAC)	Range (VAC)	Voltage (V1dc)	current (A)	Voltage (V2dc)	current (A)	
LD300E-24S12M	24	18-36	12	25			
LD300E-24S15M			15	20			
LD300E-24S24M			24	12.5			
LD300E-24S28M			28	10.71			
LD300E-24S36M			36	8.33			
LD300E-24S48M			48	6.25			
LD300E-48S12M	48	36-72	12	25			
LD300E-48S15M			15	20			
LD300E-48S24M			24	12.5			
LD300E-48S28M			28	10.71			
LD300E-48S36M			36	8.33			
LD300E-48S48M			48	6.25			
LD300E-110S12M	110	72-144	12	25			
LD300E-110S15M			15	20			
LD300E-110S24M			24	12.5			
LD300E-110S28M			28	10.71			
LD300E-110S36M			36	8.33			
LD300E-110S48M			48	6.25			
LD300E-110S12M	300	200-400	12	25			
LD300E-300S15M			15	20			
LD300E-300S24M			24	12.5			
LD300E-300S28M			28	10.71			
LD300E-300S36M			36	8.33			
LD300E-300S48M			48	6.25			



\*\*customized ,pls contact sales\*\*

**Input Specifications**

Input Voltage Range	Input Voltage Range (Vdc)		Max (Vdc)	Input Static Current (mA)				
	9-36		40	20				
	18-75		80	10				
<b>Output Specifications</b>								
Item	Min	Typ	Max	Test Conditions				
Voltage Accuracy		±1%						
Voltage Adjust Rate		±0.2%						
Load Regulation		±0.5%						
Auxiliary Voltage Accuracy		±3%						
Ripple&Noisy		±1%						
Temperature Regulation		±0.02%/°C						
Over Current Protect	120%		150%					
Short Circuit Protect	Burp type, self-recovery							
Dynamic Response	400μS		25% load					
<b>Gerneral Specifications</b>								
Isolation Resistor	200MΩ		Input-Output					
Isolation Voltage	1000VDC		Input-Output					
	500VDC		Input-Case					
	500VDC		Output-Case					
Switching Frequency	300KHz		Mil HDBK 217F Tc=25°C					
MTBF	200000Hrs							
Case Temperature	-40~+100°C							
Storage Temperature	-55~+125°C							
Relative Humidity	5%-90%							
Pin Solder Temperature	250°C		Soldering spot is 1.5mm away from case for 10 seconds					
Hand Soldering Time	5s		Iron Temperature 425 °C					
Temperature Coefficient	±0.02%/°C							
Shock	5G		10~55Hz					
Cooling	Free Air							
Weight	650g (Typ)							
**Unless specified, otherwise all other parameters are tested under the following conditions: nominal input voltage, pure resistive load, 25°C room temperature environment.								
<b>Dimensions and Recommended Layout</b>								



Unit:mm

**Recommended Circuit****Remark:**

Adding input capacitor CIN helps to improve electromagnetic compatibility. Electrolytic capacitor 47 uf-100uf CIN is recommended. If the module is connected to a digital circuit, add cout, cout1, cout2

**Noted**

1. Input current: Ensure that the output current of the power supply meets the instantaneous starting current of the power module (that is, twice the average input current of the power module).
2. Output load requirements: Avoid no-load use. When the actual power consumption of the load is less than 10% of the rated output power of the module or no load occurs, connect an external resistance to the output end (the sum of the external resistance and the load power is greater than or equal to 10% of the rated load) or select a module with a smaller rated power.
3. The external capacitance of the output end should not be too large; otherwise, the module may be overcurrent or poorly started. For details, see the external capacitance recommendation table.
4. External LC filter circuit can be connected for occasions with high ripple noise requirements.