

FEATURES:

- Wide input range
- Continuous short-circuit protection, self recover
- I/O isolation voltage 1.5KV
- Working temperature: $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- No additional components required
- Stable performance and high reliability (MTBF \geq 1000K hours)
- Industry standard pin-out
- Metal case
- DIP package

Selection Guide

Part No.	INPUT		OUTPUT				CapacitiveLoad(μF)
	Norminal (Vdc)	Range (Vdc)	Voltage (V1dc)	current (mA)	Voltage (V2dc)	current (mA)	
LD15-12S3X3C	12	9-18	3.3	4000			
LD15-12S05C			5	3000			
LD15-12S12C			12	1250			
LD15-12S15C			15	1000			
LD15-12S24C			24	650			
LD15-18S3X3C	18	9-36	3.3	4000			
LD15-18S05C			5	3000			
LD15-18S12C			12	1250			
LD15-18S15C			15	1000			
LD15-18S24C			24	650			
LD15-24S3X3C	24	18-36	3.3	4000			
LD15-24S05C			5	3000			
LD15-24S12C			12	1250			
LD15-24S15C			15	1000			
LD15-24S24C			24	650			
LD15-36S3X3C	36	18-72	3.3	4000			
LD15-36S05C			5	3000			
LD15-36S12C			12	1250			
LD15-36S15C			15	1000			
LD15-36S24C			24	650			
LD15-48S3X3C	48	36-72	3.3	4000			
LD15-48S05C			5	3000			
LD15-48S12C			12	1250			
LD15-48S15C			15	1000			
LD15-48S24C			24	650			
LD15-110S05C	110	40-160	5	3000			
LD15-110S12C			12	1250			
LD15-110S15C			15	1000			

LD15-110S24C		24	650		
--------------	--	----	-----	--	--

customized accepted,pls contact sales for details

Input Specifications

Input Voltage	Input Voltage Range (Vdc)	Nom(Vdc)	Max (Vdc)
	9-18	12	18
9-36	18	36	
18-36	24	36	
36-72	48	72	
18-72	36	72	
40-160	110	160	

Hot Plug Unavailable

Output Specifications


Item	Typ	Max	Test Conditions
Voltage Accuracy	±1%	±3%	0-100% load
Line Regulation	±0.2%	±0.5%	Input voltage variation from low to high at full load
Load Regulation	±0.5%	±1%	5%-100% load
Ripple&Noise	-	100mVp-p	20MHz bandwidth, 5%-100% load
Transient Recovery Time	300µs	500µs	25% load step change, Nominal input voltage
Over-voltage Protection	-	160%Vo	110%Vo(Min)
Over-current Protection	140%Io	190%Io	110%Io(Min)
Short-circuit Protection			Continuous, self-recovery

General Specifications

Switching Frequency	300KHz(Typ)	PWM mode
MTBF	1000 K hours	MIL-HDBK-217F@25°C
Temperature Coefficient	0.03%/°C	100% full load
Isolation (Input-Output)	1.5KVDC	
Insulation Resistance	1000MΩ	Input-output resistance 500Vdc
Operating Temperature	-40~+85°C	
Storage Temperature	-55~+125°C	
Storage Humidity	5-95%	Non-condensing
Cooling Method	Free air convection	
Case Material	Aluminum alloy	
Weight	12g (Typ)	

**Unless specified, otherwise all other parameters are tested under the following conditions: nominal input voltage, pure resistive load, 25°C room temperature environment.

Dimensions and Recommended Layout




Note:
Unit: mm[inch]
Pin diameter tolerances: $\pm 0.10[\pm 0.004]$
General tolerances: $\pm 0.50[\pm 0.020]$

Pins

Pin-Out	Mark		
1	+Vin		
2	-Vin		
3	GND		
4	No Pin		
5	Vo1		

Recommended Circuit



Recommended input and output capacitor values

Vin	Cin	Cout		
5	100uF/16V			
12	100uF/25V			
24	10uF/50V-47uF/50V			
48	10uF/100V-47uF/100V			

Noted

1. Input current: Ensure that the output current of the power supply meets the instantaneous starting current of the power module (that is, twice the average input current of the power module).
2. Output load requirements: Avoid no-load use. When the actual power consumption of the load is less than 10% of the rated output power of the module or no load occurs, connect an external resistance to the output end (the sum of the external resistance and the load power is greater than or equal to 10% of the rated load) or select a module with a smaller rated power.
3. The external capacitance of the output end should not be too large; otherwise, the module may be overcurrent or poorly started. For details, see the external capacitance recommendation table.
4. External LC filter circuit can be connected for occasions with high ripple noise requirements.